



INSTALLS EASILY ANY WAY YOU CHOOSE

Outlook *plus* compliant series installs easily, cleanly and securely in any situation. Choose our standard 1 1/8 inch skirt with a built-in flange or our 3/4-inch reduced skirt for recessed in-floor or on-floor installation.

DAM PROFILE (1 1/8" Skirt shown)

Finished floor
Flange
1/2"
Threshold
Skirt

Whichever unit or method you choose, code compliance comes easily. Simply ensure the top of finished floor meets the start of the sloped exterior threshold.

Once properly installed, the 1/2-inch interior and exterior beveled threshold edges of our Outlook *plus* units allow walk-in or roll-in shower access without worry. It also prevents water seepage.

ON-FLOOR INSTALLATION

Codes require max. 1/2" level change

Drain

Finished floor Subfloor

OUR 1 1/8 INCH SKIRT

Simplify your work with this unit added height for recessed in-floor or on-floor installation. A front flange provides a strong and sturdy installation that prevents cracking or bowing of the dam.

RECESSED IN-FLOOR INSTALLATION

Codes require max. 1/2" level change

Drain

Finished floor Subfloor

ON-FLOOR INSTALLATION

Codes require max. 1/2" level change

Drain

RS REDUCED SKIRT

Finished floor Subfloor

OUR 3/4 INCH REDUCED SKIRT

Perfect for common 3/4-inch finished floor applications. A front flange provides a strong and sturdy installation that prevents cracking or bowing of the dam.

ACCESS RAMP

Same height

Drain

1 1/8" Skirt shown

Ramp Subfloor

ACCESS RAMP

A code-compliant access ramp, when installed according to its manufacturer's guidelines, can also be used with either product or installation methods.